

## Mini instantaneous water heater DHM

### For team victory.

---

The DHM mini instantaneous water heater supplies a single draw-off point where hot water is required infrequently and in small volumes. It heats the water very quickly at a DHW output of up to two and a half litres per minute. Its small dimensions enable flexible installation even in the tightest of spaces. The DHM is suitable for undersink installation. It is installed with commercially available pressure taps.

### The most important features

The most efficient DHW provision at the washbasin

For a single draw-off point

3.5/4.4/5.7 kW (subject to model)

2.0 - 3.3 l/min (subject to model)

230 V with connecting cable

Bare wire heating system

For pressure-tested installation with pressure taps

Undersink installation





Type	DHM 3	DHM 4	DHM 6	DHM 6 220
Type	DHM 3	DHM 4	DHM 6	DHM 6 220
Part no.	220813	220814	185473	220815
Rated output	3,50 kW	4,40 kW	5,70 kW	5,70 kW
Height	143 mm	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm	82 mm
Specification				
Fuses	16 A	20 A	25 A	32 A
Specific resistance (	1100 Ohm cm	1100 Ohm cm	1100 Ohm cm	1100 Ohm cm
Conductivity at 15 °C	90 mS/m	90 mS/m	90 mS/m	90 mS/m
Weight	1,40 kg	1,40 kg	1,40 kg	1,40 kg
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Rated current	15,20 A	19,10 A	24,70 A	27,20 A
IP-Rating	IP25	IP25	IP25	IP25
Rated output	3,50 kW	4,40 kW	5,70 kW	5,70 kW
Colour	white	white	white	white
Power connection	1/N/PE ~ 230 V 50Hz	1/N/PE ~ 230 V 50Hz	1/N/PE ~ 230 V 50Hz	1/N/PE