



Electric Towel Rails

Instructions

Model Numbers covered by this manual.

4230 (75774230) HSTRL250C 250W – 230V

4130 (75774130) HSTRL250W 250W – 230V

To obtain the best performance from your towel rail, it is important to read, and follow these instructions for safe operation.

This Towel Rail is designed specifically for domestic purposes and Heatstore cannot be held responsible if used in any other type of installation.

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

Children should be supervised to ensure that they do not play with the appliance.

WARNING! *In order to avoid a hazard for very young children, this appliance should be installed so that the lowest heated towel rail is at least 600mm above the floor.*

Heatstore & Addvent , Victoria Road, Avonmouth, Bristol, BS11 9DB, United Kingdom
Website: www.heatstore.co.uk

THE TOWEL RAIL MUST BE WIRED TO COMPLY WITH THE CURRENT EDITION OF THE I.E.E REGULATIONS BY A QUALIFIED ELECTRICAL ENGINEER. THE REGULATIONS CONTAIN IMPORTANT REQUIREMENTS REGARDING SAFETY OF ELECTRICAL APPLIANCES IN BATHROOMS.

The Towel Rail cable should be connected to the electrical supply through a means for disconnection in all poles in accordance with the wiring rules. The cable connected to the appliance must be fixed wiring.

If used in a bathroom it should be connected to an unswitched fused spur outlet. In other rooms a switched unit should be used.

The Towel Rail is designed as a fixed electrical appliance for fixed wiring and must be earthed.

IMPORTANT! A 13-AMP PLUG SHOULD NOT BE FITTED TO THE MAINS LEAD.

A 3-amp fuse must be used. As the colours in the wires in the mains supply cord may not correspond with the coloured markings identifying the connection terminals, make the electrical connections as:-

- The GREEN/YELLOW earth wire to the terminal marked \oplus or "E".
- The BROWN (L) live wire to the terminal marked "L".
- The BLUE (N) neutral wire to the terminal marked "N".

MOUNTING INSTRUCTIONS

Your Towel Rail is supplied with the required number of mounting brackets; **mounting instructions** are detailed on the bracket fixing pack.

It is vital that the towel rail is installed with the heating element supply cable **at the bottom of the rail.**

SAFETY

This equipment has been designed and manufactured to the highest international standards, but like all electrical appliances that are operated by mains voltage, care must be taken if you are to obtain the best results and safety is to be assured.

- DO NOT use the appliance if damaged.
- If the supply cord is damaged, it **MUST BE** replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.
- DO NOT use the appliance to carry articles that have been cleaned with dry cleaning fluids.
- DO NOT use the appliance to carry articles that have been in contact with oil or petroleum based products.
- DO NOT use the appliance unless it has been fitted to the wall as per these instructions.
- DO NOT install the Towel Rail immediately below a socket outlet.

The container of this heater is filled with a precise quantity of special heat transfer fluid. Any leakage must be reported to the manufacturer, its service agent or similarly qualified person. The system is sealed, and any attempt to break the seals will invalidate the warranty

CLEANING

To clean the Towel Rail, polish with a clean dry cloth when the Towel Rail is switched off.

If a more thorough clean is required, the use of non-abrasive wax polish (similar to those used to polish car paintwork) will help to maintain the chromium finish).

Under no circumstances should any kind of abrasive or spray cleaner be used to clean the Towel Rail.

These may contain chemicals, which can affect the surface finish and as such may invalidate your warranty.

IF YOUR TOWEL RAIL DOES NOT WORK

Check that the fuse has not blown at the flex outlet, or at the distribution board.

DO NOT attempt to repair the Towel Rail.

Should none of the above remedies work, then consult an accredited service agent.

If the appliance is still under guarantee, return it to your supplier or contact our after sales service.

HEATSTORE AFTER SALES SERVICE

We offer a technical advisory service to contractors and other customers with problems in the field.

RING: "0117 923 5375" / E-MAIL: "enquiries.heatstore@adivision.co.uk"

GUARANTEE

This Towel Rail is guaranteed against defects for 1 year from the date of purchase.

Heatstore reserves the right to repair or replace the Towel Rail.

